



CMA 150.8

8 channel Class D power amplifier

- 8 input and output channels
- Switching power Class-D circuitry
- Individual channel volume control & signal/clip LED indicators
- Perfect solutions for multi-zone low-Z speakers with space saving 1U design

Model	CMA 150.8	
Power (RMS All channels Driven)	4Ω (RMS) 8Ω (RMS)	130W x 8 70W x 8
Input Sensitivity (limiter off)	0.9 - 1.1V (+0 / -1 dBV)	
Input Impedance	20kΩ balanced / 10kΩ unbalanced	
Frequency Response (4Ω)	100Hz - 15kHz (+0/-1 dB)	
Voltage Gain	28 (+/-0.5dB)	
THD + N (ref 1kHz, 1/8 rated power, A-Weighted)	<0.1%	
S/N Ratio (ref 1kHz, A-Weighted)	> 95dB	
Crosstalk (below rated power)	> 70dB	
Damping Factor (1kHz, 8Ω)	> 200	
Power / output circuitry	Switching Power Class D	
Protections	Full short circuit, open circuit, thermal, ultrasonic & RF protection stable into reactive or mismatched loads, turn ON/OFF, muting	
Controls	Front: ON/OFF power switch Rear: Volume Channel 1-8	
Indicators	Power x1, Signal / Protection / Clip x 8 channels	
Connectors	Input : Euroblock / Output : Euroblock	
Power Supply	AC: 110-120V or 220-240V 50/60Hz	
Dimensions (W x D x H)	483 x 360 x 44 mm	
Weight	6.3 kg	

Specifications subject to modification without notice

